برنامه نویسی سیستمی

Microsoft


Windows Internals

كاوه حقيقي

مفاهيم سختافزار

قطعات كامپيوتر

- پردازنده
- رم یا حافظه اصلی
- هارد یا حافظه جانبی
 - کارت گرافیک
 - كارت شبكه
 - مادر برد
 - پاور یا منبع تغذیه
 - موس و کیبورد
- مانیتور یا صفحه نمایش




كامپيوتر چيست؟

2 به علاوه 2 میشه 4

اگر ساعت 5 بود بوق بزن

What is Computer








کاوه حقیقی – برنامه نویسی سیستمی

پردازنده چیست؟









واحد پردازشگر مرکزی







زبان کامپیوتر



فضای ذخیرهسازی



حافظه اصلی Ram



مادربرد – مین برد




پردازنده گرافیکی




کاوه حقیقی – برنامه نویسی سیستمی


كارت شبكه




منبع تغذيه








کاوه حقیقی – برنامه نویسی سیستمی







Plug (Male)	Socket (Female)	Name	Format/Use	Found On
		VGA (15-Pin D-Sub) 17mm x 8.5mm	Analogue Video Although largely replaced by DVI, VGA inputs and outputs are still common on laptops and TVs.	Personal Computers, Monitors, Projectors & Televisions.
		Mini VGA 10.6mm x 5mm	Analogue Video Not to be confused with Mini-DisplayPort, this older Apple connection is making a comeback on tablets and netbooks	Select Tablets & Laptops

DVI				Available in lengths from
Plug (Male)	Socket (Female)	Name	Format/Use	Found On
	∜ (DVI-A (Analogue) 25mm x 8mm	Digital or Analogue Video Signals are compatible with both VGA (analogue)	Personal Computers, Monitors & Televisions.
	•	DVI-D Dual Link (Digital) 25mm x 8mm	and HDMI (digital) for easy conversion. This is the only common standard that includes both digital and analogue signals. Connectors can range from 12+5 to 24+5	Personal Computers, Monitors & Televisions.
	Q	DVI-I Dual Link (Integrated Analogue and Digital) 25mm x 8mm	pins. The flat pin on a DVI-I male connecter is wider than the same pin on a DVI-D connector.	Personal Computers, Monitors & Televisions.
	************	Mini DVI (Integrated Analogue and Digital) 11.2mm x 7.1mm	Digital or Analogue Video Supports up to 1920x1200 resolution for compatiblity with HDMI, VGA and DVI (single link) Replaced by Mini- DisplayPort	Select Apple computers and laptops

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
A COLUMN TO A COLU		Type A 13.9mm x 4.45mm	Digital Video + Audio (& Ethernet v1.4) HDMI is the latest commercial standard for	Modern Televisions, Monitors, Laptops, Blu- ray, DVD, PVR, Projectors X-Box 360, PS3, Persona Computers & more!
		Type C (Mini HDMI) 10.42mm x 2.42mm	high-definition digital video and audio signals in the one connection. v1.3 cables are capable of current-generation high-definition and 3D output, while v1.4 will cater to the next-gen 2k x 4k super-high definition and even better 3D signals along with wired network support.	Camcorders, Digital Cameras, Notebooks, Tablet PCs and other small A/V devices.
		Type D (Micro HDMI) 6.4mm x 2.8mm		Tablet PCs, Camcorders, Digital Cameras and other miniaturized A/V devices.

Plug (Male)	Socket (Female)	Name	Format/Use	Found On	
			Digital Video	<u> </u>	
		DisplayPort 16mm x 4.5mm	Designed to replace DVI and VGA	Apple PCs and Laptops,	
			Thunderbolt Multi-purpose Data transfer.	Computer Monitors and PC Video Cards/GPUs.	
		Thunderbolt uses the same form factor and plug type as Mini-			
10		Mini-DisplayPort & Thunderbolt	DisplayPort, but expands the standard to support use for file transfer, Firewire and more.	Apple Notebooks and	
	7.5mm x 4.5mm	* Not all Mini-DispalyPort sockets are Thunderbolt compatible!	Netbooks.		

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
		TOSLINK (S/PDIF Digital Optical) 7mm x 6mm	TOSLINK is a compact and convenient method of carrying high-quality	CD, DVD, Blu-ray, Personal Computers & Gaming Consoles Socket is commonly found with a flap/door covering to protect against dust and dirt.
	4)))	Mini-TOSLINK (3.5mm Digital Optical) 14.5mm x 3.5mm	digital audio signals over fibre optic cable. Digital Optical connections are a popular auxiliary output for when quality matters.	Apple Computers, MiniDisc Players & other personal audio devices. Socket can be easily confused with 3.5mm stereo audio jack.

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
Gen	•	2.5mm Stereo Audio Jack (TRS Connector) 11mm x 2.5mm		Pocket PCs and other miniaturized PDA devices
	U	2.5mm Mono Audio Jack (TRS Connector) 11mm x 2.5mm	Analogue Audio (Stereo or Mono) TRS stands for Tip, Ring, Sleeve', and describes	Sometimes found on telephone headsets.
San		3.5mm Stereo Audio Jack (TRS Connector) 14mm x 3.5mm	the three-part construction that carries the stereo left, stereo right and ground currents respectively. They have been the ubiquitous audio connection for most of	Personal Computers, Laptops, Headphones, MP3 players, Mobile
E.	0	3.5mm Mono Audio Jack (TRS Connector) 14mm x 3.5mm	the last century, and offer high audio quality for headphones and small stereo speakers. Analogue Audio or Video (Stereo plus Mic) TRRS jacks have an extra	Phones, PDAs, DVD Players, Radios and mud morei
Cities.		3.5mm 4-Pole Audio Jack (TRRS Connector) 14mm x 3.5mm	connection, typically for microphone input but sometimes used for composite video. They are the same physical size as a regular jack and are most common in the 3.5mm pin size.	Smartphones, Microphone Headsets, Balanced Audio, In-Car AV systems.
	C	6.5mm Stereo Audio Jack (Quarter-Inch TRS Connector) 30mm x 6.5mm	TRS, TRRS and Himi-TOSLINK ports can be easily coefused (expecially on Apple products), and are not always compatible with each other.	High-end Stereo Headphones, A/V and Stereo Receivers,
	U	6.5mm Mono Audio Jack (Quarter-Inch TRS Connector) 30mm x 6.5mm		Aviation Headsets, Moin, Decks and other audio equipment.

کاوه حقیقی – برنامه نویسی سیستمی

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
	Pares Pares COMPONENT VIDEO	Component Video (YPbPr) 15mm x 12mm	High Definition Analogue Video Supports up to 1080p video, and is typically combined with Left & Right RCA Audio.	Receivers, Televisions, Media Players, etc.
- T	Video R L	Composite Video with Left & Right Audio 15mm x 12mm	Standard Definition Analogue Video Supports up to 480i (720 x 576i) video, plus stereo (L&R) audio.	Receivers, Televisions, VCRs, Laserdiscs, Old- School Consoles and A/V Equipment
See Se	COAXIAL	Digital Coaxial Audio (S/PDIF) 15mm x 12mm	High Quality Digital Audio Supports Dolby Digital and DTS Audio up to 7.1 surround sound.	Receivers, Televisions, Media Players, and other high-end audio equipment.
	LINE IN L G R	Subwoofer RCA (1RCA to 2RCA) 15mm x 12mm	Left & Right Stereo Audio / Dedicated Subwoofer Channel For Analogue Stereo Audio and connecting amplifiers/receivers to subwoofers with 2 RCA Inputs	Subwoofers, Stereo Amplifiers, DVD Players

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
and the same of th		SCART (EIA Multiport) 43mm x 13mm	Standard Definition Video and Audio Common in European devices and some Foxtel units.	Foxtel Boxes & some TV's
		S-Video (SVHS, Y/C) 6mm x 8.5mm	Analogue Video S-Video is still found as an auxiliary input or output on many types of AV Equipment.	Laptops, VCRs, Set Top Boxes, DVD Players, Receivers and Televisions, etc. Not to be confused with PS/2 ports for keyboards and mice.

JSB Available in lengths from 50cm to 5

USB	n2R					
Plug (Male)	Socket (Female)	Name	Format/Use	Found On		
		USB Type A (Standard A USB) 12mm x 4.2mm	Data Transfer & Gadget Charging USB cables are	USB Flash Drives, USB Novelty Gadgets, Media Players, Computers, Printers, Laptops, etc.		
		USB Type B (Standard B USB) 8mm x 7mm	everywhere these days. There's a size and a type for everything, from flash drives to external sound cards, and from printers to camcorders. If it has data on it, or can be charged at low voltage, it's likely going to have at	External Hard Drives, Printers, etc.		
		Mini USB 4 Pin (USB Mini-B) 4.5mm x 3.5mm	Proprietary Design USB Connectors If your USB cable / socket does not look like any listed here, it is possible	Kodak Cameras, Other Digital Cameras, etc.		
	<i></i>	Mini USB 5-Pin (USB Mini-B) 7mm x 3mm	your device features one of many non-standard 'proprietary' USB connectors, where the shape of the connector is modified by a manufacturer to prevent the use of standard USB	Cameras, Portable Hard Drives, Mobile Phones, Portable Media Players, etc.		
		Micro USB (USB Micro-B) 7mm x 2mm	cables. In such cases, you may need to contact the product supplier for a suitable USB cable.	Mobile Phones & some Android Smartphones, Tablets, GPS and other miniature electronic devices		
	USB 3.0	USB 3.0 Type A 12mm x 4.2mm	Data Transfer & Gadget Charging	Personal Computers, External Hard Drives & High Speed PC Peripherals.		
	US8 3.0	USB 3.0 Type B 8mm x 10.5mm	Designed to be backwards compatible where possible, USB 3.0 can be identified by the blue plastic spacers and sometimes by additional connector pins attached to common USB 2.0	External Hard Drives, Printers and other high- speed devices		
	***	USB 3.0 Micro B 12.5mm x 2mm	shaped sockets.	External Hard Drives, Cameras and other high- speed devices		
		USB 3.1 Type-C (USB-C) 8.2mm x 2.4mm	Super-Speed 10Gbps US8 Type-C can have many abilities from fast data transfer to carrying power and multimedia signals.	Newer Smartphones, PCs, Laptops and Apple computers		

کاوه حقیقی – برنامه نویسی سیستمی

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
		Speaker Cable & Binding Post	Speaker Audio Speaker wire terminals	
		Banana Plug & Binding Post 17mm x 4mm	are typically optional, with bare wire to a binding post offering one less 'link in the chain' between devices. Banana plugs may appear tidier and are easier to remove and replace on equipment	Loudspeakers, Subwoofers, Amplifiers, Receivers, Audio Switches, Mixing Decks and other high-end audio equipment.
		Speaker Wire & Push-Terminals (Grip Connector)	that is moved or changed regularly.	

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
TO	BNC	BNC (RF Coaxial) 13.5mm (diam)	Analogue Video & Networking Largely replaced by RCA and digital alternatives.	Network adaptors, radio antennas, closed-circuit and other specialist video equipment.
		F-Type (F Connector) 8,5mm x 10,5mm	Radio Frequency & Data Transfer Cable Internet and Terrestrial Television can run over F-Type connections.	Cable Modems, Foxtel and other Cable Television sources, TV Aerials, etc.
		TV Aerial (Belling-Lee / PAL TV) 8.5mm x 9mm	Radio Frequency & Data Transfer European & Australian standard for Terrestrial Television antenna connections.	Televisions, Roof Antennas, Radio Receivers, etc.

کاوه حقیقی – برنامه نویسی سیستمی

Computer Cables Available in lengths from 50cm to 5m

(Male)	Socket (Female)	Name	Format/Use	Found On
	MINE WHEN	SATA Data (Serial ATA) 14mm x 3.5mm	Internal Hard Drive I/O Data Has largely replaced IDE cables for internal computer hard drive data access.	SATA Hard Disk Drives and PC Motherboards. (SATA 1, 2 & 3 compatible)
		SATA Power (Serial ATA) 24mm x 3.5mm	Internal Hard Drive Power Replaces 4-pin Molex connectors (below) on newer hard drives.	SATA Hard Disk Drives. (SATA 1, 2 & 3 compatible)
	I LEATA I	eSATA (External Serial ATA) 14.5mm x 4.5mm	External Hard Drive Deta I/O High speed data transmission (3Gb/s) for external devices.	External/Portable Hard Drives and HDO Caddies, etc. (SATA 1, 2 & 3 compatible)
		IDE (ATAPI) 54.5mm x 6mm	Internal Disk Drive Data 1/0 Max 133 MB/s data rate for optical and hard disc drives.	IDE Hard Drives, Floopy Drives, CO and DVD ROM Drives, PC Motherboards.
1555	nue	Molex Power 21mm × 6,5mm	Internal PC Peripheral Power Ubiquitous power feed between PSUs and PC components.	Hard Disk Drives, Fan Controllers, DVD ROM Drives, etc.
W	122	ROM Audio (Internal SP/DIF) Smm x 2.5mm	Direct Digital Audio This cable facilitates music playback on ROM drives that don't feature Digital Audio Extraction.	Internal PC DVD- and CD- ROM Drives.
	a	Firewire 400 4-Pin (IEEE 1394b 4-Pin) 5.5mm x Jmm	Real-Time High-Speed Data Transfer Also known as i.LINK and Lynx, the Firewise	
P		Firewire 400 6-Pin (IEEE 1394a 6-Pin) 11mm x 6mm	standard is typically used on digital audio, digital video and data storage devices for PC and Apple computers. Potential speeds range between 400 and 3200 Mb/s: Plug types can be	Apple Notebooks and Computers, Digital Video Cameras and Camcorders, Data Storage Devices and External Hard Drives.
		Firewire 800 (IEEE 1394 9-Pin) 10mm x 7.5mm	converted using adapters, and run at the rate of the slowest port capacity.	
	00	PS/2 (6-Pin Mini-DIN) 6mm x 8.5mm	Mouse and Keyboard I/O Now replaced by USB on new computers and laptops.	Personal Computers and other legacy PC peripherals including mice and keyboards. Don't confuse with visually similar S-Video ports.

Plug (Male)	Socket (Female)	Name	Format/Use	Found On
Cas	11	Australian Mains Power (AS 3112 / Type I) 20mm x 39mm	Mains Power Also common in an unearthed version with only two angled pins.	Australian Mains Power Points, Powered consumer white goods and electronic devices.
		IEC Power (IEC C13 / C14) 23mm x 26mm	Mains Power S-Video is still found as an auxiliary input or output on many types of AV Equipment.	PCs, Televisions, Monitors, Amps, UPSs, and many other electronic devices.

Communications & Networking Available in lengths from 3				
Plug (Male)	Socket (Female)	Name	Format/Use	Found On
		Ethernet RJ45 (8P8C / LAN / Cat5 / Crossover) 11.5mm x 6.5mm	Network Data Transfer Capable of speeds up to 100 Gbit/sec for local area networks Cable colours vary.	PCs, Laptops, Modems, Ethernet Routers and Switches, Blu-ray Players, Gaming Consoles, etc.
	BALL	Australian Telephone Jack (600 Series) 41.5mm x 10.5mm	Telephone Slowly being phased out and replaced by RJ12 sockets (below).	Older model Telephones and Fax machines.
		RJ12 Telephone Jack (6P4C Modular) 9mm x 6mm	Telephone Found on all modern home and office telephony equipment including faxes.	ADSL & Dial-Up Modems, Telephones, Faxes and other telephony equipment.

Pro Audio Available in lengths from 50cr				
Plug (Male)	Socket (Female)	Name	Format/Use	Found On
		XLR Connector (XLR3) 16-18mm x 13mm	Balanced Audio Connector High quality microphone connection.	Microphones and performance music equipment.
To		Speakon 20mm x 17mm	High Current Professional Audio For connecting microphones to loudspeakers and amplifiers.	Microphones, loudspeakers, amplifiers and performance music equipment.
	MIDI OUT/IN	MIDI (Musical Instrument Digital Interface) 10mm x 12.5mm	Musical Instrument Communications Allows synchronisation between instruments and computers.	Keyboards, synthesizers audio controllers, mixers and other specialised computer hardware.



کاوه حقیقی – برنامه نویسی سیستمی



OPERATING SYSTEMS







DESKTOP






Ram vs Rom

Random Access Memory

Read Only Memory



روند اجرای نرم افزار













همروندی، هسته و ترد در پردازنده








هسته و ترد در پردازنده



Single core hyperthreading CPU (2 logical CPU's / threads)










انواع پردازنده





انواع پردازنده



- نسل پردازنده
- تعداد هسته
- حافظه کش



انواع پردازنده

- سری Athlon
- سری Ryzen
- سری Threadripper
 - Ryzen 3 •
 - Ryzen 5 •
 - Ryzen 7 •
 - Ryzen 9 •





انواع مادربرد






انواع پردازندههای گرافیکی






پردازندههای گرافیکی انویدیا





تفاوت CPU و GPU

Difference between GPU and CPU Cores



- CPUs have few strong cores
- Suited for serial workloads
- Designed for general purpose calculations






- Suited for parallel workloads
- Specialize in graphics processing

CGDIRECTOR.COM

CODIRECTOR

انواع رم




DDR1
 1333MH

DDR2
 3200MH

DDR3
 1100MH

DDR4
 4600MH

DDR5
 1666MH



انواع حافظه ذخيره سازى

HDD 3.5"

